



Features

- 17" color TFT LCD
- Fanless Design
- Intel Celeron N2930 1.83GHz Processor (E3845 Processor for option)
- Onboard 2GB DDR3L
- 9~36V DC Wide-ranging Power Input
- 5 Sides IP65
- 5-wire Resistive Touch Screen

Specifications

System	
Processor	Onboard Intel Celeron Quad Core N2930(1.83GHz) E3845(1.91GHz) for option
System Chipset	SoC
System Memory	Onboard 2GB DDR3L SDRAM Onboard 4GB DDR3L SDRAM for option
Storage	1 x 2.5" HDD Space 1 x Internal SD slot onboard

External I/O	
USB	3 x USB 2.0 type A 1 x USB 3.0 type A
Serial/Parallel	1 x RS-232/422/485 DB-9 selectable, Default RS-485, COM1 2 x RS-232 DB-9, COM2 and COM3
Audio	2 x Line-out, phone jack
LAN	2 x GbE LAN RJ-45
Power	1 x 3-pin terminal block connector 1 x Power Switch on/off


Expansion	
On board expansion bus	1 x Mini PCIe full size Optional WiFi/BT with Antenna

LCD	
Display Type	17" TFT LCD
Max. Resolution	1280 x 1024
Max. Color	16.7M
Contrast Ratio	1000:1
Luminance (cd/m ²)	350
View Angle	H: 170 / V: 160
Backlight Lifetime	30,000 hrs

Touch Screen	
Type	Resistive Touch Window
Interface	USB
Light transmission (%)	80%

Power	
Power input	9~36V DC
Power Consumption	MAX: 21.9W

Dimensions



UNIT: mm
Tolerance: ±0.5

Mechanical	
Chassis Color	Stainless Steel Chassis
IP Rating	5 sides IP65 with I/O cover
Mounting	VESA Mount 75x75
Dimension	432 x 358 x 55 mm
Net Weight	7.3Kg

Environmental	
Operating temperature(°C)	0~50°C
Storage temperature(°C)	-30°C~70°C
Storage humidity	10 to 90% @ 40°C, non- condensing
Certificate	CE / FCC Class A

Operating System Support	
Windows 7 Professional for Embedded Systems, Windows Embedded 8.1 Pro, Windows Embedded 8.1 Industry pro Windows 10 IoT-E(Pro)	

Technische Änderungen und Irrtum ohne Vorankündigung vorbehalten! Alle Rechte geschützt!



WETIF Industrie EDV
Senserstraße 3
D - 82140 Olching

Telefon DE +49 8142 448976-1
Telefax DE +49 8142 448976-4
Internet www.WETIF.com

Telefon AT +43 664 2868223
Telefax AT +43 662 234661844
eMail info@wetif.com