



DT311C/ DT311T

Rugged Tablets

Slim, Rugged, Multi-functional Wireless Computing

The DT311 Series Rugged Tablets feature the integration of high brightness 11.6" capacitive touch screens and high performance, energy-efficient Intel® processors within slim, lightweight, durable packages. With built-in smart card/CAC reader, Wi-Fi and Bluetooth as well as options for front/ back cameras, barcode scanner, GNSS, and 4G connection, these robust tablets offer seamless information capture and transmission for improved workflow. Rated IP65 and MIL-STD-810G certified with wide temperature range (-20°C to 60°C), the DT311 Series Rugged Tablets provide reliable operation in harsh, mission-critical environments.



Features

- 11.6" high-brightness capacitive touch screen (800 nits), digital pen support
- Intel® Celeron® or 8th Generation Core™ i5/i7 processor
- Microsoft® Windows® 10 IoT Enterprise operating system
- Built-in SD card reader, 2nd USB port or HDMI-out port
- High capacity, hot-swappable battery pack
- IP65 rated, MIL-STD-810G and MIL-STD-461F certified
- Build-in smart card/ CACreade

Major Options

- RS-232 port
- Front and back cameras
- Barcode scanner
- U-blox M8 GNSS module
- 4G LTE/AWS

Specifications



Model	DT311C	DT311T
System		
CPU	Intel® Celeron® processor	Intel® 8 th Generation Core™ i5 or i7 quad-core processor
RAM	8GB	8GB to 16GB
Storage	256GB Flash	256GB to 2TB Flash
Operating System	Microsoft® Windows® 7 Professional or Windows® 10 IoT Enterprise	Microsoft® Windows® 10 IoT Enterprise
Display	11.6" LED-backlight screen with capacitive touch	
Display Resolution	1920 x 1080	1920 x 1080
Fan/ Fanless	Fanless	Fanless
Control Switch and Buttons	1 power button, 1 trigger button, 3 programmable buttons, 1 RF switch	
Indicator	1 power/ battery status LED	1 power/ battery status LED
Microphone	Built-in microphone with DSP for real-time video	
Speaker	Built-in speaker	Built-in speaker
Network Interface		
WLAN	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band	
Bluetooth	Bluetooth 4.2 LE	Bluetooth 4.2 LE
I/O Ports		
USB Ports	USB 3.0 X 1	USB 3.0 X 1
Headset Jack	1 (3.5mm)	1 (3.5mm)
DC-in	1	1
Ethernet	1 RJ45 connector for Ethernet	1 RJ45 connector for Ethernet
Smart Card/CAC Reader	Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card	
SD Slot*	1 full size SD card slot. *Can be changed to 1 USB 2.0 port or 1 HDMI-out port	

Mechanical and Environmental

AC/DC Adapter	Input: 100-240V AC; Output: 19V DC, 3.42A	
Battery Pack	Hot swappable battery, 3.7V, 8800mAh	Hot swappable battery, 11.4V, 5400mAh; Hot swappable battery, 11.4V, 8000mAh (optional)
Enclosure	ABS + PC plastics and magnesium-aluminum alloy	
Protective Bumpers	Rubber bumpers on each corner for handling protection	
Dimensions (H x W x D)	8.3 x 12.4 x 0.86 in/ 212 x 316 x 21.9 mm	8.3 x 12.4 x 0.86 in/ 212 x 316 x 21.9 mm
Weight	3.5 lbs/ 1.6 kg	3.5 lbs/ 1.6 kg
Durability	IP65, MIL-STD-810G and MIL-STD-461F certified	
Regulatory	FCC Class B, CE, RoHS compliant	
Temperature	Operation*: -20°C to 60°C (-4°F to 140°F), tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety, optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F). Storage: -55°C to 70°C (-67°F to 158°F)	
Humidity	0%–90% non-condensing	

Major Options

Barcode Scanner	2D scanner, reads 1D also	
Camera	2 megapixel front camera, and 8 megapixel back camera	
GNSS Module	U-blox M8 GNSS module with concurrent reception of GPS and GLONASS; industry leading -167dBm navigation sensitivity	
I/O Port Module	RS-232 port, 6-pin lockable connector included	
Mobile Broadband	4G LTE/AWS	4G LTE/AWS

* Specifications subject to change without notice.

Technische Änderungen und Irrtum ohne Vorankündigung vorbehalten! Alle Rechte geschützt!

Accessories

Digital Pen

Pen Tip	Diameter: 0.059 in/ 1.5mm, replaceable
Buttons	2 side buttons (right-click and eraser)
Battery	1 AAAA, replaceable
Color	Black
Dimensions	Length: 5.5 in/ 140 mm (including pen tip) Diameter: 0.38 in/ 9.7 mm
Weight	0.055 lbs/ 25 g



Desktop Charging Cradle

Docking support with ports for Power, USB, HDMI outputs and Ethernet



Detachable Keyboard

Designed to connect to a DT Tablet, instantly pairs, ideal for 2-in-1 applications.



Tablet Mount Cradle

Offers Tablet storage and security with power, HDMI-out, COM, Ethernet pass-through, and USB ports. Power supply is not included



5-Bay Cabinet Charger

Multi-tray charger, capable of charging up to 5 tablets simultaneously



Battery Charging Kits



Carrying Case



High Capacity Battery Pack



WETIF Industrie EDV
Senserstrasse 3
D - 82140 Olching

Telefon +49 8142 448976-0
Telefax +49 8142 448976-4
Mobil +49 172 817 44 11

Email info@wetif.com
Internet www.wetif.com