



DT301Y/ DT311Y/ DT313Y Rugged Tablets

Slim, Rugged, Multi-Functional Wireless Computing

The DT301Y, DT311Y and DT313Y Rugged Tablets feature the integration of high-brightness 10.1", 11.6" and 13.3" touchscreens and high performance, energy-efficient Intel® Core™ or Pentium® processors within slim, lightweight, durable packages. With built-in smart card/CAC reader and Wi-Fi as well as optional data capture modules, these robust tablets offer seamless information capture and transmission for improved workflow. Rated IP65, MIL-STD-810G/461F and HERO certified with a wide temperature range, the DT301Y, DT311Y and DT313Y Rugged Tablets provide reliable operation in harsh, mission-critical environments.



Features

- 10.1", 11.6" or 13.3" sunlight readable touchscreen, digital pen supported
- Intel® Core™ i5/i7 or Pentium® Gold 7505 processor
- Microsoft® Windows® 10/11 IoT Enterprise operating system
- NIST compliant BIOS available
- IP65-rated for water and dust resistance
- MIL-STD-810G for shock and vibration protection
- MIL-STD-461F for EMI and EMC tolerance
- HERO (Hazard of Electromagnetic Radiation to Ordnance) certified
- Built-in smart card/CAC reader
- Antimicrobial coating
- Detachable keyboard option for 2-in-1 applications
- Energy Star 8.0 certified (DT301Y and DT311Y)

Major Options

- Front and back cameras
- Barcode scanner
- UHF RFID reader
- GPS module
- 4G LTE/AWS

Specifications



Model	DT301Y	DT311Y	DT313Y
System			
CPU	Intel® Pentium® Gold 7505, 2-Core, up to 3.5 GHz Intel® Core™ i5-1135G7, 4-Core, up to 4.2 GHz Intel® Core™ i7-1165G7, 4-Core, up to 4.7 GHz	Intel® Core™ i5-1135G7, 4-Core, up to 4.2 GHz Intel® Core™ i7-1165G7, 4-Core, up to 4.7 GHz	Intel® Core™ i5-1135G7, 4-Core, up to 4.2 GHz Intel® Core™ i7-1165G7, 4-Core, up to 4.7 GHz
RAM	8GB to 32GB		
Storage	256GB to 2TB Flash		
Operating System	Microsoft® Windows® 10/11 IoT Enterprise		
NIST Compliance	NIST Compliant BIOS Available		
Display	10.1" LED-Backlit, Sunlight Readable (800 nits) Touchscreen	11.6" LED-Backlit, Sunlight Readable (1000 nits) Touchscreen	13.3" LED-Backlit, Sunlight Readable (1000 nits) Touchscreen
Display Resolution	1920 x 1200	1920 x 1080	
Internet	Wi-Fi 802.11ax, 2.4/5/6 GHz Dual Band		
BT	5.2	5.2	5.2

I/O Interface

AC/DC Adapter	Input: 100-240V AC; Output: 19V DC, 3.42A		Input: 100-240V AC; Output: 20V DC, 3.25A
Speaker	Built-In Speaker		
Microphone	Built-In Microphone		
USB Ports	1 x USB 3.0, 1 x USB Type-C	1 x USB 3.0, 1 x USB Type-C	3 x USB 3.0, 1 x USB Type-C
Ethernet Port	1 x Ethernet 10/100/1000MB Base-T LAN		
Headphone Jack	1 (3.5 mm)	1 (3.5 mm)	1 (3.5 mm)
DC IN Jack	1	1	1
Smart Card/CAC Reader	Full-Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card		
Switches & Buttons	1 x Power Button; 2 x Brightness Buttons; 5 x Programmable Buttons		

Mechanical and Environmental

Enclosure	ABS + PC Plastic and Magnesium-Aluminum Alloy		
Battery Pack	Hot-Swappable Battery (11.4V, 5400mAh) Hot-Swappable Battery (11.4V, 8000mAh)(Optional)		
Dimensions (H x W x D)	7.8 x 11 x 0.86 in/198 x 280 x 21.9 mm	8.3 x 12.4 x 0.86 in/212 x 316 x 21.9 mm	10.6 x 13.2 x 0.8 in/270 x 335 x 21 mm
Weight	2.86 lbs/1.3 kg	3.5 lbs/1.6 kg	3.97 lbs/1.8 kg
Temperature	Operation*: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) *For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) Storage: -55°C to 70°C (-67°F to 158°F)		
Humidity	0% – 90% Non-Condensing		
Certifications	FCC Class B, CE, RoHS Compliant		
Durability	IP65, MIL-STD-810G and MIL-STD-461F Certified		IP65 and MIL-STD-810G Certified
Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing	Yes	Yes	N/A

Major Options

Barcode Scanner	2D Barcode Scanner (Reads 1D & 2D)		
Camera	2MP Front Camera & 8MP Back Camera		
UHF RFID Reader	865 – 928 MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; 16 ft (4.87m) Reading Distance	865 – 928MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; 30 ft (9.14m) Reading Distance	N/A
GNSS Module	GPS Module with Concurrent Reception of GPS and GLONASS; Industry Leading - 167dBm Navigation Sensitivity		
Mobile Broadband	4G LTE/AWS	4G LTE/AWS	4G LTE/AWS

* Specifications subject to change without notice.

Technische Änderungen und Irrtum ohne Vorankündigung vorbehalten! Alle Rechte geschützt!



WETIF Industrie EDV
Senserstrasse 3
D - 82140 Olching

Telefon +49 8142 448976-0
Telefax +49 8142 448976-4
InfoTel +49 8142 448976-3

Email info@wetif.com
Internet www.wetif.com