

Fanless hi-power Thin Client Mini PC: FI300

4th Gen. Intel® Core® i5 Processor
Intel® HD Graphics 4400
Dual DisplayPort 1.2
COM / USB3.0 / TPM
mSATA, Mini PCIe 3G and WiFi



KEY FEATURES



Fanless Silent Operation
 Fanless design, enjoy quiet environment.



DisplayPort 1.2
 Supports PC resolutions up to 2560x1600 @60Hz stereoscopic 3D graphics and all HDTV resolutions including 1080p. also supports daisy chaining of multiple monitors. Features a maximum total throughput of up to 21.6Gbps.



Energy Saving
 Low power consumption saves money and better for the environment.



Full HD 1080p
 Enjoy a cinema-quality movie watching experience in the comfort of your own home.



Gigabit LAN
 High-speed LAN connection with 1Gb/s data transfer rate. Ideal for seamless internet connection for audio and video streaming.



USB3.0
 Maximum transmission speed of up to 5Gb/s (10X faster than USB2.0), ideal for connecting to external hard drives.



TPM (Trusted Platform Module)
 Onboard TPM offers enhanced platform security through top level encryption; mandated by many IT departments.



VESA Mount (not included)
 Save more space by mounting the Mini PC behind your LCD or TV designed to fit seamlessly into any environment any lifestyle.



RoHS Compliant

SPECIFICATIONS

Dimension	10.3in x 6.9in x 1.4in 260mm x 175mm x 35mm
Processor	Intel® Core™ i5-4200U Processor, 2 Cores / 4 Threads 1.6GHz, Max Turbo Frequency 2.6GHz, Max TDP 15W
Chipset	Integrated into CPU
Display	Intel® HD Graphics 4400 Microsoft® DirectX® 11 Dual DisplayPort 1.2 with audio support
Memory	Not included One SO-DIMM slot, up to 16GB of DDR3L 1600 MHz
Storage	Not included Support 2.5inch SATA SSD or HDD
Audio	Realtek® High Definition Audio (5.1) Digital audio via DisplayPort 1.2 connector 1x Audio out & S/PDIF combo jack on the front panel 1x Mic in jack on the front pane
Ethernet	1x Realtek® Gigabit Ethernet Controller 1x Rj45 port on the back panel
Wireless	Not included, optional IEEE 802.11 b/g/n module
IR	Onboard IR module An infrared sensor on the front panel 1x 3.5mm audio jack for extended infrared sensor Not included Remote Control(Optional)
Expansion Slots	1x SIM Card slot 3x Mini-PCI Express® (Full-length for mSATA SSD; Full-length for PCIE/USB /3G; Half-length for PCIE)
Peripheral interfaces	4x USB3.0 (two on the back panel) 2x USB2.0 (on the back panel) 2x COM Port (one on the back panel) 1x DC-IN jack (19V /12V)
OS Support	Windows® 7, 8.1 und Linux
System BIOS	AMI EFI BIOS; ACPI
Cooler	Fanless Heatsink
Operating Temperature	0° to +35° C

Technische Änderungen und Irrtum ohne Vorankündigung vorbehalten! Alle Rechte geschützt!



WETIF Industrie EDV
 Senserstraße 3
 D - 82140 Olching

Telefon DE +49 8142 448976-0
 Telefax DE +49 8142 448976-4
 Mobil DE +49 172 8174411

Mobil AT +43 664 2868223
 eMail: info@wetif.com
 Internet: www.wetif.com